F4Z FDX-B, M2Z
Round Electronic pair 30 mm Ø

Product Description

With a diameter of 30mm and weighing only 6.3 grams, the M2Z/F4Z electronic pair is ideal for application on cattle and deer. The tag guarantees security, usability and high retention, while the free rotation design promotes rapid wound healing and maximises retention, as well as minimising abrasion of the animal's ear.

The single use tag has a tamperproof closing mechanism, any attempt to separate the male tag from the female would damage both parts making the product impossible to be re-used.

The F4Z FDX-B contains an FDX-B transponder, the RFID code is unique and cannot be falsified. It is not affected by normal electromagnetic interference or X-rays and can be read through any non-conductive material.

Tag numbers are laser marked as per customer's indication with a black durable contrast. The tag is available in a wide range of colours and is ideal for official identification programs as well as herd management.



Technical Specifications

Dimension (Ø)	F4Z & M2Z: 30 mm with a 60° metal tip
Weight	F4Z: 4.2 g M2Z: 2.1 g
Material	Polyurethane
Technology	FDX-B
Working Frequency	134.2 kHz
Certifications	ISO 11784/5 (964025) Full ICAR (A069) PAS44
Reading Distance	33 cm with the XRS2 EID stick reader 82 cm with the XRP2 and large antenna
Applicator	Z Tags No-Tear-Tagger™ Z Tags Universal Tagger Z Tags Tissue Tagger

Although the information presented in this Product Information Sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumedby Datamars. Performance data is typical only and variations due to component manufacturing tolerances are normal. Datamars reserves the right at any timeto change performance characteristics or specifications without prior notice. © Datamars 2021– All rights reserved.